

KATADYN GROUP

CAPE HORN EXTREME 330R WATERMAKER

PRODUCT SPECIFICATIONS

330 gal (1249 l) Production / Day Production / Hour 15 gal (56 l)

12 V DC 19A | 24 V DC 10A 16 Watts/1 gal | 4.2 Watts/1 liter Power Requirement

95 lbs (43 kg) Weight

Pre Filters 2.5" x 10" pleated polyester 5 micron

Controls Spectra Remote Manual Controller

Dedicated thruhull, dry and well ventilated area not to exceed 110°F/37°C Installation Requirements

Membranes 40" x 2.5" High rejection spiral wound

polyamide

Pump and Motor Shurflo diaphragm pump

Salt Rejection 99.2%

Max 110°F/37°C Min 36°F/2°C Temperature Range

33.000 PPM feed water at 77°F/25°C **Baseline Conditions**

pH Range 3-11 (typical seawater pH is 8)

Chlorine Tolerance O PPM

Warranty Spectra standard warranty

Shipping Weight 115 lbs (52 kg) 47" x 23" x 18" Shipping Dimensions

120 cm x 59 cm x 46 cm





FACTS

The Cape Horn family continues to be the choice for serious offshore racing campaigns like the Volvo Ocean Race and Clipper Challenge round-the-world yachts. The Cape Horn Extreme 330 is reliable and durable, with its diaphragm feed pumps in parallel, it can be run on a single pump for high efficiency or two pumps for high output. The Cape Horn 330 features Manual Remote control with Spectra's simple and reliable controller. This simplified controller can be mounted remotely and offers basic control of the watermaker, including freshwater flush with a set duration, perfectly bridging the gap between our full manual and completely automated watermaker systems. Add the Automated Z±ION Membrane Protection System to extend storage times for up to 30 days.

FEATURES

- Remote Manual control system offers basic watermaker control at a distance Optional "tank full" cut-off switch
- Freshwater flush control with a set duration
- Compact modular design
- Spectra's unique Clark Pump for efficiency and reliability
- High and low speed operation for customizable power management and output volume
- Low power consumption—can be run on batteries, solar, or wind power
- Commercial grade diaphragm pumps with run dry protection
- System includes installation kit, handheld water quality tester, and product sample valve
- Z±ION Compatible



CAPE HORN EXTREME 330R WATERMAKER




4" / 10.2 cm **Remote Manual Control Panel** Depth 0.6" / 1.5 cm



Remote Monitoring Panel Depth 1.6" / 4.1 cm





Secondary Feed Pump Module

Depth 6" / 5.2 cm

44" / 112 cm High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm

OPTIONAL COMPONENTS



Z±ION System Protection, Automated Z±ION-AUTO

Spectra Watermakers reserves the right to modify products

Katadyn Desalination LLC.

Spectra Watermakers 2220 S McDowell Blvd Ext Petaluma, CA 94954

TEL: 1-415-526-2780 FAX: 1-415-526-2787 E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com