

VENTURA 200R-T WATERMAKER

PRODUCT SPECIFICATIONS

200 gal (757 l) Production / Day Production / Hour 8.3 gal (31 l)

Power Requirement

12 V DC 10A | 24 V DC 5A 17 Watts/1 gal | 4.5 Watts/1 liter

65 lbs (29.4 kg) Weight

Pre Filters 2.5" x 10" pleated polyester 5 micron

Controls Analog controls

Dedicated thruhull, dry and well ventilated area not to exceed 110°F/37°C Installation Requirements

Membranes 20" x 2.5" High rejection spiral wound

polyamide

Pump and Motor Shurflo diaphragm pump

Salt Rejection 99.2%

Max 110°F/37°C Min 36°F/2°C Temperature Range

Baseline Conditions 33.000 PPM feed water at 77°F/25°C

pH Range 3-11 (typical seawater pH is 8)

Chlorine Tolerance O PPM

Warranty Spectra standard warranty

Shipping Weight 85 lbs (38.5 kg) Shipping Dimensions 36" x 25" x 21"

91 cm x 63 cm x 53 cm







FACTS

The same size as the Ventura 150, but designed for warm water above 50°F (10°C), the Ventura 200R-T delivers over 8 gallons (31 liters) per hour. With its modular design, it's an ideal system for installation in tight spaces whether you're cruising or racing. The Ventura 200R-T teatures Manual Remote control with Spectra's simple and reliable controller. This simplified controller can be mounted remotely and offers basic control of the watermaker, including freshwater Tulob with a set duration, perfectly bridging the gap between our full manual and completely automated watermaker systems. Add the Z±ION Membrane Protection System to extend storage times for up to 30 days.

FEATURES


- Optimized for high output performance in warm water (over 50°F/10°C)
- Remote Manual control system offers basic watermaker control at a distance Freshwater flush control with a set duration
- Controller gives tank full indication when used with a tank switch
- Compact modular design
- Spectra's unique Clark Pump ensures efficiency and reliability
- Low power consumption—can be run on batteries, solar, or wind power
- Commercial grade diaphragm pumps with run dry protection
- System includes installation kit, handheld water quality tester, and product sample valve
- Z±ION compatible



VENTURA 200R-T WATERMAKER



Feed Pump Module Depth 4.5'' / 11.4 cm





Remote Monitoring Panel Depth 1.6" / 4.1 cm



9.3" 23.5 cm

Pre-Filter Depth 6" / 15.2 cm



27.3" / 69.2 cm High Pressure Clark Pump and Membrane Depth 12" / 30.5 cm

OPTIONAL COMPONENTS



Z±ION System Protection, Automated Z±ION-AUTO

Katadyn reserves the right to modify products

Katadyn Desalination LLC.

Spectra Watermakers 2220 S McDowell Blvd Ext Petaluma, CA 94954

TEL: 1-415-526-2780 FAX: 1-415-526-2787 E-MAIL: sales@spectrawatermakers.com

www.spectrawatermakers.com